



- ① FINISHED LANDSCAPING GRADE.
- ② RAIN BIRD 44RC QUICK COUPLING VALVE OR APPROVED EQUAL.
- ③ 1" PVC NIPPLE, SCHEDULE 80.
- ④ PVC ELBOWS, SCHEDULE 80.
- ⑤ PVC TEE.
- ⑥ SPRINKLER SUPPLY LINE.
- ⑦ CARSON 910 PLASTIC VALVE BOX OR EQUAL WITH LOCK BOLT.
- ⑧ PEA GRAVEL: 6" DEEP BELOW QUICK COUPLING VALVE.
- ⑨ BRICKS: 2 TOTAL

NOTE:

INSTALLATION OF SWING JOINTS SHALL BE ON A 45° ANGLE TO HORIZONTAL. ALL PIPES AND FITTINGS SHALL BE PVC SCHEDULE 80.

THE CITY OF WEST SACRAMENTO – STANDARD DETAIL

APPROVED BY:  CITY ENGINEER C-38733 P.E. NO. 3/31/05 DATE

REVISION:	
REVISION:	
REVISION:	
REVISION:	

TITLE:
QUICK COUPLING VALVE W/ DOUBLE SWING JOINT
 STANDARD DETAIL #: 715

